

HFP SERIES Fixed Pulverizers



The Hydraram HFP-Pulverizer is specially designed for the secondary demolition and recycling. The shape of the jaws of the crusher is designed to pick up and crush concrete as effectively as possible.

Interchangeable teeth are standard on all models. The steel cutters in the back of the pulverizers' jaw can cut reinforcement steel easily.

This tool is made out of the most durable steel HARDOX-400® with an extremely high wear resistance, resulting in minimum maintenance and a long lifespan.

The installed speed multiplier valve ensures fast work cycles.



| FIXED PULVERIZERS | | | HFP-4V | HFP-7V | HFP-15V | HFP-22V |
|---|------------------------------|-------|-----------|-----------|-----------|-----------|
|  | Excavator class ¹ | t | 4 - 7 | 6 - 10 | 13 - 19 | 18 - 28 |
|  | Weight | kg | 500 | 740 | 1420 | 2180 |
|  | Jaw opening | mm | 465 | 530 | 730 | 825 |
|  | Cutter length | mm | 140 | 140 | 220 | 260 |
|  | Working pressure | bar | 320 | 320 | 350 | 350 |
|  | Oilflow | l/min | 80 - 150 | 80 - 150 | 120 - 200 | 200 - 300 |
|  | Open/close | sec. | 2.8 / 3.2 | 3.4 / 5.3 | 2.0 / 2.6 | 2.0 / 2.7 |

| FIXED PULVERIZERS | | | HFP-28V | HFP-35V | HFP-48V | HFP-72V |
|---|------------------------------|-------|-----------|-----------|-----------|-----------|
|  | Excavator class ¹ | t | 25 - 35 | 33 - 45 | 42 - 68 | 65 - 85 |
|  | Weight | kg | 2820 | 3420 | 4760 | 6980 |
|  | Jaw opening | mm | 870 | 950 | 1130 | 1250 |
|  | Cutter length | mm | 260 | 260 | 300 | 325 |
|  | Working pressure | bar | 350 | 350 | 350 | 350 |
|  | Oilflow | l/min | 250 - 350 | 300 - 400 | 350 - 500 | 450 - 600 |
|  | Open/close | sec. | 3.0 / 3.2 | 2.8 / 2.7 | 2.6 / 2.9 | 3.0 / 3.7 |

¹ Recommended excavator / attachment combination

