

HSF-B SERIES

Pile Drivers



PILE DRIVERS			HSF-3B	HSF-10B	HSF-20B	HSF-30B	HSF-40B	HSF-60B	HSF-80B	HSF-120B
	Excavator class ¹	t	4 - 8	8 - 10	10 - 12	12 - 15	15 - 20	25 - 30	38 - 40	45 - 50
	Weight	kg	160	375	610	635	650	1210	1610	2350
	Dynamic weight	kg	120	290	495	515	530	1000	1290	1700
	Working pressure	bar	150	320	320	320	320	300	350	300
	Oilflow	l/min	30	100	110	110	110	210	253	315
	Centrifugal force	kN	33	81	258	297	449	349	464	934
	Eccentric moment	kgm	0.35	1	2	3	4	6	8	12.6
	Speed	rpm	3000	3200	3200	3000	3200	2300	2300	2600
	Pulling force	kN	15	30	60	60	60	120	150	200
	Push down	kN	15	20	40	40	40	80	90	200
	Amplitude	mm	5.5	6	9	12	15	12	13	14.8
	Power	kW	9	60	60	60	60	123	148	185
	Length	mm	505	700	770	770	770	928	1130	1093
	Width	mm	191	451	511	511	511	621	641	720
	Height	mm	790	1096	1215	1215	1215	1631	1750	2100

¹ Recommended excavator / attachment combination

